



**PDU - 1,5U  
Standart**

Anodized aluminium profile body  
16 A, 250 V AC (50-60 Hz)  
Maximum power 3500 W  
Earthing contact socket outlets  
(German type)  
Socket inserts set at 45°  
2 mt. 3x1,5 mm<sup>2</sup>, earthed cord, black  
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
7010 - 103	3 sockets
7010 - 106	6 sockets
7010 - 109	9 sockets
7010 - 112	12 sockets

**Optional**

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock



**PDU - 1,5U  
Two-phased On-Off Switch  
(illuminated)**

Anodized aluminium profile body  
16 A, 250 V AC (50-60 Hz)  
Maximum power 3500 W  
Earthing contact socket outlets  
(German type)  
Two-phased on-Off switch (illuminated)  
Socket inserts set at 45°  
2 mt. 3x1,5 mm<sup>2</sup>, earthed cord, black  
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
7020 - 103	3 sockets, On-off switch
7020 - 106	6 sockets, On-off switch
7020 - 109	9 sockets, On-off switch
7020 - 112	12 sockets, On-off switch

**Optional**

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock



**PDU - 1,5U  
Overload Protection**

Anodized aluminium profile body  
16 A, 250 V AC (50-60 Hz)  
Maximum power 3500 W  
6 earthing contact socket outlets  
(German type)  
Overload Protection  
Socket inserts set at 45°  
2 mt. 3x1,5 mm<sup>2</sup>, earthed cord, black  
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
7030 - 106	6 sockets, Overload protection

**Optional**

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock