PDU - 1,5U

6 Sockets (German type)
Two-phased On-Off Switch
(illuminated), Overload Protection

Anodized aluminium profile body
16 A, 250 V AC (50-60 Hz)
Maximum power 3500 W
6 Earthing contact socket outlets
(German type)
Two-phased on-Off switch (illuminated)
Overvoltage Protection
Socket inserts set at 45^0
2 mt. 3x1,5 mm^2, earthed cord, black
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
7040 - 106	6 sockets, On-off switch, Overload protection

Optional

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock

PDU - 1,5U

Overload Protection
Surge Protection

Anodized aluminium profile body
16 A, 250 V AC (50-60 Hz)
Maximum power 3500 W
Earthing contact socket outlets
(German type)
Overvoltage Protection
Surge Protection
Socket inserts set at 45^0
2 mt. 3x1,5 mm^2, earthed cord, black
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
7050 - 106	6 sockets, Overload protection, Surge protection
7050 - 109	9 sockets, Overload protection, Surge protection

Optional

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock

PDU - 1,5U

Overload Protection
Surge Protection
Two-phased On-Off Switch (illuminated)

Anodized aluminium profile body
16 A, 250 V AC (50-60 Hz)
Maximum power 3500 W
Earthing contact socket outlets
(German type)
Overload Protection
Surge Protection
Two-phased On-Off Switch (illuminated)
Socket inserts set at 45^0
2 mt. 3x1,5 mm^2, earthed cord, black
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
7060 - 06	6 sockets, Overload protection, Surge protection, On-Off Switch
7060 - 109	9 sockets, Overload protection, Surge protection, On-Off Switch

Optional

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock