



**PDU - 19" 1U**  
**Miniature Circuit Breaker (MCB) (1P)**

Anodized aluminium profile body  
16 A, 250 V AC (50-60 Hz)  
Maximum power 3500 W  
Earthing contact socket outlets  
(German type)  
Miniature circuit breaker (MCB) (1P)  
Socket inserts set at 45°  
2 mt. 3x1,5 mm², earthed cord, black  
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
8080 - 103	3 sockets, MCB (1P)
8080 - 104	4 sockets, MCB (1P)
8080 - 105	5 sockets, MCB (1P)
8080 - 106	6 sockets, MCB (1P)

**Optional**

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock



**PDU - 19" 1U**  
**Overload Protection**

Anodized aluminium profile body  
16 A, 250 V AC (50-60 Hz)  
Maximum power 3500 W  
Earthing contact socket outlets  
(German type)  
Overload protection  
Socket inserts set at 45°  
2 mt. 3x1,5 mm², earthed cord, black  
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
8030 - 105	5 sockets, Overload protection
8030 - 106	6 sockets, Overload protection
8030 - 107	7 sockets, Overload protection
8030 - 108	8 sockets, Overload protection

**Optional**

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock



**PDU - 19" 1U**  
**Overload Protection**  
**by Reset On-Off Switch**

Anodized aluminium profile body  
16 A, 250 V AC (50-60 Hz)  
Maximum power 3500 W  
Earthing contact socket outlets  
(German type)  
Overload Protection by Reset On-Off Switch  
Socket inserts set at 45°  
2 mt. 3x1,5 mm², earthed cord, black  
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
8040 - 105	5 sockets, Overload protection by reset on-off
8040 - 106	6 sockets, Overload protection by reset on-off
8040 - 107	7 sockets, Overload protection by reset on-off
8040 - 108	8 sockets, Overload protection by reset on-off

**Optional**

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock