



PDU - 19" 1U
Two-phased On-Off Switch
(illuminated), Surge Protection

Anodized aluminium profile body
16 A, 250 V AC (50-60 Hz)
Maximum power 3500 W
Earthing contact socket outlets
(German type)
Two-phased on-Off switch (illuminated)
Surge protection (page 381)
Socket inserts set at 45°
2 mt. 3x1,5 mm², earthed cord, black
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
8050 - 104	4 sockets, On-off switch, Surge protection
8050 - 105	5 sockets, On-off switch, Surge protection
8050 - 106	6 sockets, On-off switch, Surge protection

Optional

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock



PDU - 19" 1U
Overload Protection Switch
Surge Protection

Anodized aluminium profile body
16 A, 250 V AC (50-60 Hz)
Maximum power 3500 W
Earthing contact socket outlets
(German type)
Overload Protection Switch
Surge protection
Socket inserts set at 45°
2 mt. 3x1,5 mm², earthed cord, black
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
8060 - 104	4 sockets, Overload protection switch, Surge protection
8060 - 105	5 sockets, Overload protection switch, Surge protection
8060 - 106	6 sockets, Overload protection switch, Surge protection

Optional

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock



PDU - 19" 1U
Overload Protection
Surge Protection

Anodized aluminium profile body
16 A, 250 V AC (50-60 Hz)
Maximum power 3500 W
Earthing contact socket outlets
(German type)
Overload Protection
Surge Protection
Socket inserts set at 45°
2 mt. 3x1,5 mm², earthed cord, black
IP 20

TS IEC 60884-1 and TS 40

Item Number	Specification
8070 - 104	4 sockets, Overload protection, Surge protection
8070 - 105	5 sockets, Overload protection, Surge protection
8070 - 106	6 sockets, Overload protection, Surge protection

Optional

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock