PDU - 19" 1U LED
1 Socket (German type)
Two-phased On-off Switch (illuminated)

Anodized aluminium profile body
16 A, 220-240 V AC (50-60 Hz)
Maximum power 3500 W
1 Earthing contact socket outlet (German type)
Two-phased on-Off switch (illuminated)
LED : 800 lumen
Socket insert set at 45^0
Mounting with brackets (at both sides)
2 mt. 3x1,5 mm^2, earthed cord, black
IP 20

Item Number	Specification
8920 - 901	LED, 1 socket , On-off switch
8920 - 951	LED, 1 socket , On-offs witch, Door position switch

Optional

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock

PDU - 1U LED
Two-phased On-off switch (illuminated)

Anodized aluminium profile body
16 A, 220-240 V AC (50-60 Hz)
Maximum power 3500 W
Two-phased on-Off switch (illuminated)
LED : 700 lumen
Mounting with brackets (at both sides)
2 mt. 3x1,5 mm^2, earthed cord, black
IP 20

Item Number	Specification
8930 - 902	LED, On-off switch

Optional

- Mobile mounting with magnets inside (at both sides)
- Cordless
- Child lock

PDU - 1U LED
2 Sockets (German type)
Two-phased on-Off switch (illuminated)

Anodized aluminium profile body
16 A, 230 V AC (50-60 Hz)
Maximum power 3500 W
2 Earthing contact socket outlets (German type)
Two-phased on-Off switch
LED : 550 lumen
Socket insert set at 45^0
Mounting with brackets (at both sides)
2 mt. 3x1,5 mm^2, earthed cord, black
IP 20

Item Number	Specification
8940 - 902	LED, 2 sockets, On-off switch

Optional

- C13, C14, C19, C20 types of socket inserts and plugs (IEC 320, BS 1363)
- Cordless
- Child lock
- Mobile mounting with magnest inside (at both sides)